

FK-508

Technische Daten | Technical Data

Empf. Mindestrastrabstand <i>rec. centre spacing</i> :	4,10 mm	.161 inches
Federkraft <i>Spring Force</i> :	0,4 N	1.38 oz.
Maximaler Federweg <i>Max. Travel</i> :	2,54 mm	.100 inches
Empfohlener Kontaktthub <i>Recomm. (rated) Travel</i> :	1,52 mm	.060 inches
Temperaturbereich <i>Temperature range</i> :	-55°C bis +250°C	-67°F to +482°F
Typischer Widerstand <i>Typical Resistance</i> :	30 mΩ	30 mΩ
Typischer Nennstrom <i>Rated Current Load</i> :	2 A	2 amps
E-Maß <i>Extension Height</i> :	7,90 mm	.311 inches
Bauform, Anschluss <i>Design, Connection Type</i> :	THT-t	

Werkstoffe | Materials

Kolben <i>Plunger</i> :	Cu-Legierung, hartvergoldet <i>Copper alloy, hardgold plated</i>
Gehäusehülse <i>Barrel</i> :	Neusilber, vergoldet <i>Nickel Silver, gold plated</i>
Feder <i>Spring</i> :	Edelstahl <i>Stainless Steel</i>

